

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
10 May 2002 (10.05.2002)

PCT

(10) International Publication Number  
**WO 02/36314 A1**

- (51) International Patent Classification<sup>7</sup>: **B26B 19/06**, 19/04, 19/38
- (21) International Application Number: PCT/US00/30063
- (22) International Filing Date:  
1 November 2000 (01.11.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
09/702,036 30 October 2000 (30.10.2000) US
- (71) Applicant: **CONAIR CORPORATION** [US/US]; One Cummings Point Road, Stamford, CT 06904 (US).
- (72) Inventors: **ABRAHAM, Paul, Andrew**; 21 Timber Ridge, Mount Kisco, NY 10549 (US). **ALMSTEAD, John, David, Jr.**; 34 Tanglewood Court, Ridgefield, CT 06877 (US). **TOBIN, Richard, Neil**; 199 Wardwell Street #3, Stamford, CT 06902 (US).
- (74) Agent: **RUGGIERO, Charles, N., J.**; Ohlandt, Greeley, Ruggiero & Perle, L.L.P., 10th Floor, One Landmark Square, Stamford, CT 06901-2682 (US).
- (81) Designated State (*national*): CA.
- Published:**  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: HAIR CLIPPER WITH PIVOTING CLIPPER HEAD ASSEMBLY



(57) **Abstract:** A hair clipper (10) having a pivoting clipper head (50) is provided. The hair clipper has a clipper head (50), a handle (20) and connectors (42) for connecting the handle and the head. The clipper head includes a stationary blade (55) having teeth and a reciprocating blade (57) having teeth, wherein the teeth of the stationary blade are substantially parallel to the teeth of the reciprocating blade forming a cutting edge (61). The handle includes longitudinal axis and a motor (30) for reciprocating the blades such that hair positioned within the teeth of the stationary blade are cut by the teeth of the reciprocating blade. The connectors the clipper head and the handle such that the clipper head pivots about an axis of rotation (A-A) that is perpendicular to the longitudinal axis of the handle and parallel to the cutting edge.



WO 02/36314 A1

## HAIR CLIPPER WITH PIVOTING CLIPPER HEAD ASSEMBLY

### BACKGROUND OF THE INVENTION

5     1.     Field of the Invention

The present invention relates to hair clippers. More particularly the present invention relates to a hair clipper having a pivoting clipper head assembly.

10    2.     Description of the Prior Art

Electric hair clippers having a stationary blade and a reciprocating blade are known in the art. The stationary blade and the reciprocating blade each have a plurality of teeth along the leading edge of the blades. The blades are mounted to the clipper such that the teeth of the stationary  
15 blade are substantially parallel to the teeth of the reciprocating blade. In this manner, reciprocating the reciprocating blade with respect to the stationary blade trims hair positioned between the teeth.

Since the leading edge of the blades present the teeth to the cutting surface, the person using the clipper must move the clipper to various  
20 angles to position the leading edge of the blades parallel with respect to the cutting surface. Thus, it is desirable to provide a hair trimmer that permits adjustment of the blades with respect to the handle to better enable the user to position the blades parallel with respect to the cutting surface.

25    **SUMMARY OF THE INVENTION**

It is an object of the present invention to provide a clipper having a clipper head assembly that is pivotable about an axis of rotation that is perpendicular to the handle and parallel to the cutting edge of the clipper head.

30       The present invention is an improved hair clipper having a pivoting clipper head assembly. The hair clipper includes a clipper head including a stationary blade having teeth and a reciprocating blade having teeth in which the teeth of the stationary blade are substantially parallel to the teeth

of the reciprocating blade forming a cutting edge. The hair clipper also includes a handle having a longitudinal axis and means for reciprocating the reciprocating blade such that hair positioned within the teeth of the stationary blade are cut by the teeth of the reciprocating blade. Connectors  
5 connect the clipper head and the handle such that the clipper head pivots about an axis of rotation that is perpendicular to the longitudinal axis of the handle and parallel to the cutting edge.

In one embodiment, the improved hair clipper has a handle with a pair of legs. Each leg has a connector disposed thereon. The clipper head  
10 has pivot points positioned on opposite sides of the head. The connectors are adapted to pivotally secure the pivot points such that the clipper head is pivotable about an axis of rotation that is perpendicular to the longitudinal axis of the handle and parallel to the cutting edge of the clipper head.

## 15 DESCRIPTION OF THE FIGURES

Fig. 1 is a top view of the clipper of the present invention;

Fig. 2 is a bottom view of the clipper of Fig. 1;

Fig. 3 is an exploded bottom view of a preferred embodiment of the clipper of Fig. 1;

20 Fig. 4 is a first side view of an alternative embodiment of the clipper of the present invention showing the clipper head in its first position;

Fig. 5 is the first side view of the clipper of Fig. 4 showing the clipper head in its second position;

25 Fig. 6 is the first side view of the clipper of Fig. 4 showing the clipper head in its third position;

Fig. 7 is the first side view of the clipper of Fig. 4 showing the clipper head in its fourth position; and

Fig. 8 is the first side view of the clipper of Fig. 4 showing the clipper head in its fifth position.

30

## DETAIL DESCRIPTION OF THE INVENTION

Referring to the figures and particularly to Fig. 1, a clipper, generally represented by reference numeral 10, is shown. Clipper 10 has a handle portion 20 and a clipper head assembly 50.

5 In a first embodiment of clipper 10, shown in Fig. 1., the clipper is a rechargeable clipper. In this embodiment, handle 20 houses a motor 30 and a battery 35.

Shown in Fig. 2, handle 20 includes an on-off switch 22, a plug 24, and a recharging indicator 26. Switch 22 has an on position and an off  
10 position. Motor 30 is operatively coupled to battery 35 when switch 22 is in the on position. Battery 35 is operatively coupled to plug 24 and recharging indicator 26 when switch 22 is in the off position. In operation, when switch 22 is placed in the on position, power flows from battery 35 to motor 30. Further, when switch 22 is in the off position, battery 35 is operatively  
15 coupled to plug 24 and recharging indicator 26 such that the plug 24 when coupled to a standard household electrical outlet delivers power to recharge the battery and to operate recharging indicator 26. Indicator 26 has a first state when battery 35 is recharging and a second state when the battery is fully recharged.

20 In this embodiment shown in Fig. 2, indicator 26 is a light emitting diode or LED 27. LED 27 has a first on or illuminated state and a second off state. In use, LED 27 is illuminated when battery 35 is recharging and the LED is off when the battery is fully recharged.

In an alternative embodiment of clipper 10 (not shown), the clipper is  
25 not rechargeable. In this alternative embodiment, handle 20 houses motor 30 operatively coupled to plug 24 when switch 22 is in the on position. In operation, switch 22 is placed in the on position to cause power to flow to motor 30 from a standard household electrical outlet coupled to a power cord, not shown, which is coupled to plug 24.

30 Referring again to Fig. 2, clipper head 50, similar to prior art clippers, includes stationary blade 55 and reciprocating blade 57. Blade 55 and blade 57 each have a plurality of teeth 60 along the leading edge of the blades. Blade 55 and blade 57 are mounted to head 50 such that teeth 60

of blade 55 are substantially parallel to teeth 60 of blade 57 forming a cutting edge 61. Motor 30 is operative coupled to reciprocating blade 57 to reciprocate blade 57 back and forth perpendicular to the longitudinal axis of handle 20. Thus, hair placed within teeth 60 is trimmed as blade 57  
5 reciprocates with respect to blade 55.

Head 50 is mounted to handle 20 so as to permit the head to pivot about an axis or rotation A. Axis of rotation A is perpendicular to the longitudinal axis of the handle and is parallel to the cutting edge 61. Preferably, axis A is offset from cutting edge 61 in the direction of handle  
10 20. Head 50 is mounted to handle 20 so as to permit motor 30 to reciprocate blade 57 as the head pivots about axis of rotation A. Thus, clipper 10 enables the user to easily position cutting edge 61 parallel to the cutting surface.

In the preferred embodiment shown in Fig. 3, handle 20 defines a pair of support legs 40. Preferably, handle 20 is forked. Each leg 40 has a connector 42 positioned along axis or rotation A. Head 50 has a pivot point 59 positioned on opposite sides of the head also positioned along axis of rotation A. Connectors 42 are adapted to secure pivotally pivot points 59 of head 50 to handle 20. Thus, connectors 42 and pivot points 59 are  
20 adapted to enable clipper head 50 to pivot about axis of rotation A.

In an alternate embodiment, shown in Figs. 4 through 8, connectors 42 and pivot points 59 are adapted to secure head 50 within handle 20 in one of a plurality of preset pivoted positions 70-1, 70-2, 70-3, 70-4 and 70-5, respectively. In this embodiment, each connector 42 includes a first gear  
25 44 and a release button 46 and each pivot point 59 includes a second gear 64. First gears 44 are connected to legs 40 so as to mesh with second gears 64 connected to head 50. Release buttons 46 are adapted to extend first gears 44 into meshing relationship with second gears 64 and are adapted to retract the first gears from the meshing relationship with the  
30 second gears. Release buttons 46 are adapted to normally mesh first gears 44 with second gears 64, thus securing head 50 in one of the preset plurality of pivoted positions. Depressing release buttons 46 unmeshes first gears 44 from second gears 64. With release buttons 46 depressed

and first gears 44 unmeshed from second gears 64, head 50 is pivotable about axis of rotation A to another one of the preset plurality of pivoted positions.

- It should be understood that the foregoing description is only
- 5 illustrative of the present invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the invention. Accordingly, the present invention is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

**WHAT IS CLAIMED IS**

1. An improved hair clipper comprising:  
a clipper head including a stationary blade having teeth and a  
5 reciprocating blade having teeth, wherein the teeth of the stationary blade  
are substantially parallel to the teeth of the reciprocating blade forming a  
cutting edge;  
a handle having a longitudinal axis and means for reciprocating the  
reciprocating blade such that hair positioned within the teeth of the  
10 stationary blade are cut by the teeth of the reciprocating blade; and  
means for connecting the clipper head and the handle such that the  
clipper head pivots about an axis of rotation that is perpendicular to the  
longitudinal axis of the handle and parallel to the cutting edge.
- 15 2. The hair clipper of claim 1, wherein the connecting means  
comprises:  
at least one leg disposed on the handle and offset from the  
longitudinal axis of the handle;  
a first connector disposed on the at least one leg; and  
20 a second connector positioned on the clipper head,  
wherein the first and second connectors join the clipper head to the  
leg of the handle such that the clipper head pivots about the axis of  
rotation.
- 25 3. The hair clipper of claim 1, wherein the connecting means is  
adapted to join the clipper head and the handle such that the clipper head  
is securable in any one of a plurality of preset pivoted positions.
4. The hair clipper of claim 3, wherein the connecting means  
30 comprises:  
at least one leg disposed on the handle and offset from the  
longitudinal axis of the handle;  
a first connector disposed on the at least one leg; and

a second connector positioned on the clipper head,  
wherein the first and second connectors join the clipper head to the  
leg of the handle such that the clipper head pivots about the axis of rotation  
and such that the clipper head is securable in any one of the plurality of  
5 pivoted positions.

5. The hair clipper of claim 4, wherein the first connector is a  
first gear, the second connector is a second gear, and the connecting  
means includes means for meshing and unmeshing the first gear and the  
10 second gear, such that when the first gear is meshed with the second gear  
the clipper head is secured in any one of the plurality of pivoted positions,  
and when the first gear is unmeshed from the second gear the clipper head  
is pivotable about the axis of rotation.

15 6. The hair clipper of claim 5, wherein the means for meshing  
and unmeshing comprises a release button adapted to mesh the first gear  
with the second gear and adapted to be depressed to unmesh the first gear  
from the second gear.

20 7. The hair clipper of claim 1, wherein the reciprocating means  
comprises a motor.

8. The hair clipper of claim 7, wherein the handle further  
comprises:  
25 a switch having an on position and an off position, and  
a cord with a plug,  
wherein the motor is operatively coupled to the cord when the switch  
is in the on position such that power flows to the motor from a standard  
household electrical outlet that receives the plug.

30 9. The hair clipper of claim 7, further comprising a rechargeable  
battery operatively coupled to the motor.



10. The hair clipper of claim 9, wherein the handle further comprises:

a switch having an on position and an off position, and  
a plug,

5 wherein the motor is operatively coupled to the battery when the switch is in the on position such that power flows from the battery to the motor.

10 11. The hair clipper of claim 10, wherein the handle further comprises:

a recharging indicator and wherein the battery is operatively coupled to the plug and the recharging indicator such that when the switch is in the off position power flows from a standard household electrical outlet that receives the plug to deliver power to recharge the battery and to operate  
15 the recharging indicator.

20 12. The hair clipper of claim 11, wherein the recharging indicator has a first state indicative of the battery recharging and a second state indicative of the battery fully recharged.

13. The hair clipper of claim 11, wherein the recharging indicator comprises an LED, said LED is illuminated when the battery is recharging and is not illuminated when the battery is fully recharged.

25 14. A hair clipper comprising:

a clipper head including pivot points positioned on opposite sides of the head, a stationary blade having teeth and a reciprocating blade having teeth, wherein the teeth of the stationary blade are substantially parallel to the teeth of the reciprocating blade forming a cutting edge; and

30 a handle having a longitudinal axis, a pair of legs, a connector disposed on each leg, and means for reciprocating the reciprocating blade such that hair positioned within the teeth of the stationary blade are cut by the teeth of the reciprocating blade,

wherein each connector is adapted to engage one of the pivot points such that the clipper head is pivotable about an axis of rotation perpendicular to the longitudinal axis of the handle and parallel to the cutting edge.

5

15. The hair clipper of claim 14, wherein the connectors and the pivot points are adapted to join the clipper head and the handle such that the clipper head is securable in any one of a plurality of preset pivoted positions.

10

16. The hair clipper of claim 15, further comprising a means for selectively releasing and securing the connectors and the pivot points such that when the connectors and pivot points are secured the clipper head is secured in any one of the plurality of pivoted positions, and when the connectors and pivot points are released the clipper head is pivotable about the axis of rotation.

15

17. The hair clipper of claim 16, wherein the connectors are first gears, the pivot points are second gears, and the releasing and securing means is adapted to release and secure the first gears with the second gears, respectively, such that when the first gears are secured with the second gears the clipper head is secured in any one of the plurality of pivoted positions, and when the first gears are released from the second gears the clipper head is pivotable about the axis of rotation.

20

25

18. The hair clipper of claim 16, wherein the releasing and securing means comprises a release button adapted to normally secure the connectors and the pivot points, and adapted to be depressed to release the connectors and the pivot points.

30

19. An electric hair clipper comprising:  
a clipper head including a stationary blade having teeth and a reciprocating blade having teeth, wherein the teeth of the stationary blade

are substantially parallel to the teeth of the reciprocating blade forming a cutting edge;




a handle having a longitudinal axis, a motor for reciprocating the reciprocating blade such that hair positioned within cutting edge are cut;

5 and






means for joining disposed on the clipper head and the handle for joining the clipper head to the handle such that the clipper head pivots about an axis of rotation that is perpendicular to the longitudinal axis of the handle, parallel to the cutting edge and offset from the cutting edge towards  
10 the handle.

20. The electric hair clipper of claim 19, wherein the means for joining is further adapted to join the clipper head and the handle such that the clipper head is securable in any one of a plurality of preset pivoted  
15 positions.

1 / 2



2 / 2

**FIG. 4****FIG. 5****FIG. 6****FIG. 7****FIG. 8**

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/30063

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : B26B 19/06; B26B 19/04; B26B 19/38  
US CL : 30/43.92

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 30/30, 31, 41.7, 41.9, 43, 43.1, 43.3, 43.91, 51, 57, 527, 528, 531, 532, 533, 534, 195, 196, 199, 208, 210, 341, DIG 1

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y, P	US 6,112,414 A (ANDIS et al) 05 September 2000 (05.09.2000), column 6, lines 39-50, see abstract and drawings.	9-13
Y, P	US 6,082,005 A (TEZUKA) 04 July 2000 (04..07.2000), column 11, lines 29-55, see abstract.	5-6 and 17-18
X --- Y	US 5,165,172 A (WEINRAUCH) 24 November 1992 (24.11.1992), column 1, lines 45-60, see abstract.	1-4, 7-8, 14-16 and 19-20 ----- 5-6, 9-13 and 17-18
X --- Y	US RE 22,638 A (KLEINMAN) 24 April 1945 (24.04.1945), columns 2-4, lines 20-40, 1-50 and 1- 10.	1-4, 7-8, 14-16 and 19-20 ----- 5-6, 9-13 and 17-18

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"

document member of the same patent family

Date of the actual completion of the international search

28 December 2000 (28.12.2000)

Date of mailing of the international search report

19 JAN 2001

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703)305-3230

Authorized officer

Rinaldi I. Rada

Telephone No. 703-308-1148

*Sheila Venev*  
**Patent Specialist**  
**Technology Center 3700**

**DERWENT-ACC-NO:** 2002-405570**DERWENT-WEEK:** 200243*COPYRIGHT 2008 DERWENT INFORMATION LTD*

**TITLE:** Electric hair clipper includes clipper head connected to handle such that clipper head pivots about rotation axis perpendicular to axis of handle and parallel to cutting edge of blades

**INVENTOR:** ABRAHAM P A; ALMSTEAD J D ; TOBIN R N**PATENT-ASSIGNEE:** CONAIR CORP[CONAN]**PRIORITY-DATA:** 2000US-702036 (October 30, 2000)**PATENT-FAMILY:**

<b>PUB-NO</b>	<b>PUB-DATE</b>	<b>LANGUAGE</b>
WO 0236314 A1	May 10, 2002	EN

**DESIGNATED-STATES:** CA**APPLICATION-DATA:**

<b>PUB-NO</b>	<b>APPL- DESCRIPTOR</b>	<b>APPL-NO</b>	<b>APPL-DATE</b>
WO2002036314A1	N/A	2000WO- US30063	November 1, 2000

**INT-CL-CURRENT:**

<b>TYPE</b>	<b>IPC DATE</b>
CIPS	B26B19/06 20060101
CIPS	B26B19/38 20060101

**RELATED-ACC-NO:** 2003-092079

**ABSTRACTED-PUB-NO:** WO 0236314 A1

**BASIC-ABSTRACT:**

NOVELTY - The hair clipper (10) includes a clipper head (50) with stationary and reciprocating blades having parallel teeth (60), and a handle (20) with a motor (30) for reciprocating the blade. The connectors connect the clipper head and handle such that clipper head pivots about a rotation axis, which is perpendicular to the longitudinal axis of handle and parallel to cutting edge of blades.

USE - Electric hair clipper with pivoting clipper head assembly.

ADVANTAGE - Provides adjustment of blades with respect to handle, as the clipper head is pivoted about an axis perpendicular to the handle and parallel to cutting edge.

DESCRIPTION OF DRAWING(S) - The figure shows the top view of the hair clipper.

Hair clipper (10)

Handle (20)

Motor (30)

Clipper head (50)

Teeth (60)

**CHOSEN-DRAWING:** Dwg.1/8



**TITLE-TERMS:** ELECTRIC HAIR CLIP HEAD CONNECT HANDLE  
PIVOT ROTATING AXIS PERPENDICULAR  
PARALLEL CUT EDGE BLADE

**DERWENT-CLASS:** P62 X27

**EPI-CODES:** X27-A02A3B;

**SECONDARY-ACC-NO:**

**Non-CPI Secondary Accession Numbers:** 2002-318412